North America - Toll Free 800.295.0220
International - 316.788.2000

**BRG**
PRECISION PRODUCTS

# 6789L Time Zone Clock
## With Date and Scrolling Message Display

www.brgprecision.com

## User Changeable Multi-Color LED Colors



Model 6789L - 4.0" time, 2.0" zone labels, 2.0" 10 character date
4.0" dot matrix message display 48" wide, 3 zones

## Specifications

| | |
|---|---|
| **Display:** | Three zone, 4 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels, 10 character date and 4"x48" scrolling message display. |
| **Zone Capacity:** | Up to 18 time zones can be displayed by page flipping zones 6 times |
| **Display Format:** | 12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date |
| **Message Display:** | The PC interface or optional Time Commander is required to make any changes to the message display. The included IR1 remote control is not connected to the message display. |
| **Clock Accuracy:** | BRG Time Zone Clocks will display the correct time for the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required. |
| **Computer Interface:** | USB interface is standard, Ethernet interface is available in lieu of the USB at no cost. |
| **Manual Controls:** | Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options. |
| **Operating Mode:** | Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets. |
| **Digit Height:** | 4.0" bar segment LEDs for time, 2.0" dot matrix LEDs for zone labels, 2.0" 20 character date and 4.0" LEDs for message display. |
| **Visibility:** | Up to 100 feet |
| **Power Requirement:** | 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard. |
| **Dimensions:** | 24.25" Tall x 60.25" Wide x 3.25" Deep |
| **Operating Temperature:** | -32$^{\circ}$ F to 120$^{\circ}$F |
| **Humidity:** | 0% to 95% Non-condensing |
| **Construction:** | Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included. |

## User Changeable Multi-Color LED Colors



| Red | Green | Blue | Yellow | Magenta | Cyan | White |
|---|---|---|---|---|---|---|